

LED Smart Conference Series Display

ISO 9001 RoHS UL ETL CE FCC CCC EMC TÜV 108" 136" 162" 216"



It integrates six major advantages:
TV / Computer / Tablet / Curtain / Audio / Projector.



TV



Stereo



Computer



Projector



Tablet



Curtain

 **4K** HD
 **conference**
 **Wireless projection**
 **Scan code to login**
 **white board**
 **Dual system**

Standardized Design

- No optical seams, Natural and even presentation, 16:9 display ratio, No stretching of the picture; low brightness and high gray, Fine and lossless picture; 2K-4K high-definition resolution, 16bit high-level grayscale, Full broadcast color gamut, High Contrast and high refresh rate, Bring more natural color reproduction ability and more extreme visual enjoyment.



High Contrast

Low Contrast



Low Grayscale

High Grayscale

Light Weight Structure

- Thin and light design, The thickness of the screen body is only 31mm, The die-casting aluminum structure design, High precision, Light weight, Good heat dissipation, Full front maintenance, Installation, No need to reserve maintenance channels, Effectively saving space.
- Support: Wall Mount / Bracket Mount.
Inputs : USD*4 HDMI 2.0*2 RJ45*1
Outputs : 3.5mm*1 audio jack SPDIF*1 HDMI*1 speaker output*1





Humanized Operation

- Support computer, mobile phone, tablet multi-platform wireless Screen projection, up to four screens can be displayed simultaneously;
- Supports screen sharing, synchronizing marked content, and more Platform terminal wireless screen projection, window, MAC OS, iOS, Android system;
- Support remote control and one-button screen projection, making meetings more convenient;
- Support the playback of multimedia files such as pictures, music, etc. 2K, 4K and other videos, compatible with multiple formats;
- Support Tencent-Cloud Audiovisual Aurora TV APK, iQiyi, Kiwi TV APK and other Android The loading of the TV version of the network TV TV APK;
- Support added microphone, camera and OPS computer;
- Support mobile phone, PAD, Computer reverse control Screen, Android, Apple are not limited;
- Support PPT, PDF, Word, Excel Conference office, etc., Convenient and fast;
- Support wireless mouse, keyboard, page turning pen, etc. HID devices;
- Support a variety of high-definition input signal detection;
- Support wired, wireless Internet access, Internet TV, Movie blockbusters to watch at any time;
- Support various welcome scene settings and calls;
- Support customized APK installation;
- Support analog optical fiber audio output, built-in power amplifier, Supports 2x15W speakers (4-8 ohms); inputs : USD*4 HDMI 2.0*2 RJ45*1

Technical parameter:(T=25°C)

Pixel Pitch	0.9375mm	1.25mm	1.5625mm	1.875mm	2.34mm
Pixel Structure	1R1G1B	1R1G1B	1R1G1B	1R1G1B	1R1G1B
Pixel Density	1137777/m ²	640000/m ²	409600/m ²	284444/m ²	182044/m ²
Module Resolution	320X180 dots	240X135 dots	192X108 dots	160X90 dots	128X72 dots
Module Size (WXH)	300X168.75mm	300X168.75mm	300X168.75mm	300X168.75mm	320X168.75mm
Specification	136" 163"	108"136"163"	108"136"163"	108"136"163"	136"163"216"
White Balance Brightness	600cd/m ²	600cd/m ²	600cd/m ²	600cd/m ²	600cd/m ²
Color Temperature	2000K—12500K	2000K—12500K	2000K—12500K	2000K—12500K	2000K—12500K
Horizontal Viewing Angle	≥160°	≥160°	≥160°	≥160°	≥160°
Vertical Viewing Angle	≥140°	≥140°	≥140°	≥140°	≥140°
Optimal Viewing Distance	≥1 m	≥1 m	≥1 m	≥1 m	≥2 m
Contrast	≥5000:1	≥5000:1	≥5000:1	≥5000:1	≥5000:1
Grayscale	12-14Bit	12-14Bit	12-14Bit	12-14Bit	12-14Bit
Refresh Rate	≥3840HZ	≥3840HZ	≥3840HZ	≥3840HZ	≥3840HZ
Continuous Working Time	≥72H	≥72H	≥72H	≥72H	≥72H
Life Span	100,000 H	100,000 H	100,000 H	100,000 H	100,000 H
Operating Voltage	DC 4.2-5V	DC 4.2-5V	DC 4.2-5V	DC 4.2-5V	DC 4.2-5V
Maximum Power Consumption	700W/m ²	700W/m ²	700W/m ²	700W/m ²	700W/m ²
Average Power Consumption	260W/m ²	260W/m ²	260W/m ²	260W/m ²	260W/m ²

Specification	108"
Wall Hanging Size (L*H*THK)	2416*1479.5*47.5mm
Floor Installation (L*H*THK)	2416*2283*723mm
Total Weight	145kg

Specification	136"
Wall Hanging Size (L*H*THK)	3016*1817*47.5mm
Floor Installation (L*H*THK)	3016*2621*732 mm
Total Weight	192kg

Specification	163"
Wall Hanging Size (L*H*THK)	3616*2154.5*47.5mm
Floor Installation (L*H*THK)	3616*2978.5*723 mm
Total Weight	265kg

Specification	216"
Wall Hanging Size (L*H*THK)	2048(W) *1152 (H)
Floor Installation (L*H*THK)	4816*2829.5*47.5 mm



Tel (INT): 86-0755 8219 7586

Add.: 1001, Building 1, Guole Technology Park, No. 1
Lirong Road, Longhua District, Shenzhen, Guangdong, China

Website (INT): www.crtop-led.com

SHENZHEN CRTOP CO., LTD.